



SOLID FLOORING

JRT Engineered Flooring comes in range of size. Choose what's		No Choice Here we recommend Reclaimed Teak as the wood that has the strength and inherent natural durability to withstand the harsh climates.	
best for you.		Our Standard Size	
(Profile (T&G)	Thickness & Core	15mm T&G Profile	9mm Arrow Profile
	3		
Profile (Arrow)	3	Varied	Fix width
	Width	Boards are mixture of fixed widths, providing more variety; Although you have to Match end when laying.	All boards are same width easier when laid down.
	4	S Incre	smental \$\$ Fix \$\$\$
	Length	Boards are between We c	ut the boards to h the center es between
	Texture 6	Non Patina Rugged Patina	Bright Patina Classico Patina
	Want to make it better	Finish with our non-Toxic Wo	od Finishes

Rubio Monocoat

SOLID RECLAIMED TEAK FLOORING









Solid Reclaimed Teak Flooring - Non Patina

Standard size: 15mm x 140-200mm x 800-2000mm

- Tounge & Groove (T&G)
- Non patina finish

Code : A020001-NP

Solid Reclaimed Teak Flooring - Rugged Patina

Standard size: 15mm x 140-200mm x 800-2000mm

- Tounge & Groove (T&G)
- · Rugged patina finish

Code : A020002-RP

Solid Reclaimed Teak Flooring – Bright Patina

Standard size: 15mm x 140-200mm x 800-2000mm

- Tounge & Groove (T&G)
- · Bright patina finish

Code : A020003-BP

Solid Reclaimed Teak Flooring - Classico Patina

Standard size: 15mm x 140-200mm x 800-2000mm

- Tounge & Groove (T&G)
- Classico patina finish

Code : A020004-CP

SOLID RECLAIMED TEAK FLOORING



Solid Reclaimed Teak Flooring - Bright Patina

Standard size: 9mm x 140-220mm x 600-2000mm

- Arrow
- Bright Patina finish

Code : A020005-BP